



Bearing No. 型号	Dimensions millimeters 尺寸 mm						Weight 重量	
	d	B	dk	r	V dp	V dmp		
					max	max	≈kg	
TK 3	3	+0.012	6 -0.12	7.93	0.3	0.012	0.009	0.0015
TK 4	4	+0.012	7 -0.12	9.53	0.3	0.012	0.009	0.0025
TK 5	5	+0.012	8 -0.12	11.11	0.3	0.012	0.009	0.0038
TK 6	6	+0.012	9 -0.12	12.7	0.3	0.012	0.009	0.0054
TK 8	8	+0.015	12 -0.12	15.88	0.4	0.015	0.011	0.0103
TK 10	10	+0.015	14 -0.12	19.05	0.4	0.015	0.011	0.0170
TK 12	12	+0.018	16 -0.12	22.23	0.4	0.018	0.014	0.0260
TK 14	14	+0.018	19 -0.12	25.4	0.5	0.018	0.014	0.0383
TK 16	16	+0.018	21 -0.12	28.58	0.5	0.018	0.014	0.0533
TK 18	18	+0.018	23 -0.12	31.75	0.5	0.018	0.014	0.0716
TK 20	20	+0.021	25 -0.12	34.93	0.6	0.021	0.016	0.0938
TK 22	22	+0.021	28 -0.12	38.1	0.6	0.021	0.016	0.1212
TK 25	25	+0.021	31 -0.12	42.86	0.6	0.021	0.016	0.1695
TK 30	30	+0.021	37 -0.12	50.8	0.6	0.021	0.016	0.2777
TK 35	35	+0.025	43 -0.12	57.15	0.6	0.025	0.018	0.3756
TK 40	40	+0.025	49 -0.15	66.6	0.6	0.025	0.018	0.6114
TK 50	50	+0.025	60 -0.2	82.5	0.6	0.025	0.018	1.1426

Type: TK..

Bearing steel, hardened, ground, polished

轴承钢, 淬火, 磨加工, 抛光

Type: TK..H

Bearing steel, hardened, ground, polished, chrome plated

轴承钢, 淬火, 磨加工, 抛光, 镀硬铬

Type: TK..S

Stainless steel, hardened, ground, polished

不锈钢, 淬火, 磨加工, 抛光